

FenceSentry Distributed Acoustic Sensor

DETECTOR UNIT (FRONT AND REAR VIEW)



PROCESSOR UNIT (REAR VIEW ONLY)



Datasheet disclaimer: All product specifications, statements, information and data in this datasheet (or made available on the website,) are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

PROCESSOR UNIT SPECIFICATIONS

PROCESSOR UNIT SPECIFICATIONS

Main Processor	AIMB-787G2
Processor	Intel i7 10700
BIOS	AMI 64 Mbit SPI
Memory: RAM	16GB
Memory	1 TB Solid State Drive 2*1 TB HDD (as RAID1)

GRAPHICS

Graphics Card	GeForce GTX1650
---------------	-----------------

INTERFACES

USB	Front: 2 , Rear: 4
Serial	Rear: 1
PS/2	Front: 1 (keyboard) / Rear: 2 (1 x keyboard and 1 x mouse)
HDMI / DVI / Displayport	Yes (1 of each)
VGA	No
Ethernet	2x connection to FenceSentry DU, 1x user connection (network switch / SCADA etc.) 1x reserved (remote login / maintenance)

ELECTRICAL

Input Voltage	AC 100 ~ 240 V
Power Consumption	300W
Power Supply Safety	UL / TUV / CB / CCC
Power Supply MTBF	100,000 hours @ 25 °C

PHYSICAL

Dimensions	482mm x 450mm x 177mm (4U)
Shipping Dimensions	610mm x 330mm x 560mm
Weight	12.5 kg (18kg Shipping weight)
System Fan Detail	1 (12 cm / 77 CFM)

ENVIRONMENTAL

Temperature	Operating: 0° to +40 °C Storage -20 ° to 60°C
Humidity	Operating: 10 ~ 85% @ 40°C, non-condensing Storage: 10 ~ 95% @ 40°C, non-condensing
Vibration (5 ~ 500 Hz)	Operating: 1Grms / Non-Operating: 2 G
Shock	Operating: 10 G (with 11 ms duration, half sine wave) / Non-Operating: 30 G

OPERATING SYSTEM AND SOFTWARE

Operating System	Windows 11 Pro
Software	DASCM

DETECTOR UNIT SPECIFICATIONS

FENCEENTRY DETECTOR UNIT SPECIFICATIONS

Range per channel* 5km or 10km

Number of channels 2

Ordering Part Numbers DAS-SNT-03-05-02CH/FS System
DAS-SNT-03-10-02CH/FS System

DATA ACQUISITION

Acquisition Frequency 10 to 2,000 Hz

Event accuracy resolution 1 to 5m

OPTICAL

Laser Wavelength 1550 nm

Optical Budget 5 dB

Connector Type FC / APC

Cable type Single mode 9/125

Cable Installation Method Fence Mounted (See installation guide)

Bandweaver Cable FenceLine as standard, Other cables available on request

Laser Safety Classification Class 1

ELECTRICAL AND HARDWARE INTERFACES

Supply Voltage 100V-240V AC

Power Consumption 30W (typical) / 40W (max)

Relays 20 Relays outputs plus 2 on/off inputs

Serial RS485 to control additional relays

PHYSICAL

Dimensions 431mm x 384mm x131mm (3U)

Shipping Dimensions 570mm x 530mm x 320mm

Weight 10 kg (13.8kg Shipping Weight)

IP Rating IP40

Material Painted Steel

Colour/Finish Matt Black

Shipping dimensions 570 x 330 x 540 mm

Shipping Weight 15 kg

ENVIRONMENTAL

Operating Temperature -10° to +55°C

Operating Humidity 0 to 95% RH, Non-condensing

Storage Temperature -10°C to +85°C

Storage Humidity 0 to 95% RH, Non-condensing

SAFETY AND APPROVALS

Laser Safety IEC60825-1

CE - EMC EMC 2014/30/EU - EN 61000-6-3:2007+A1:2011

EN 61000-3-2:2014

EN 61000-3-3:2013

EN 61000-6-1:2007

CE - LVD LVD 2014/35/EU - IEC 61010-1:2010

EN 61010-1:2010

CE - RoHS Yes

FDA FDA Ascension number 2422248-000

FCC 47CFR Part 15:2017

ANSI C63.4:2014

*Range is dependent on the optical quality of the sensing cable route. This can be confirmed upon reviewing an OTDR trace vs the planned optical budget.

The above specifications are provided as guidance only and cannot be guaranteed to be exact, and Bandweaver will supply the equivalent or better.

